




WEMCO[®] Self-Primer[™]



440 West 800 South • P.O. Box 209
Salt Lake City, UT 84110-0209
Tel: 801-359-8731 • Fax: 801-355-9303
www.weirsp.com • info@weirsp.com



WEMCO[®] Self-Primer[™] Pump Details



Pump Size	6" x 6" • 152 mm x 152 mm ANSI/DIN
Pump Casing	Ductile Iron
Operating Pressure	Maximum 120 psi (797 kPa)
Impeller	Open type, two vane. Material - Ductile Iron Pumps 3" (76.2 mm) solids
Impeller Shaft	17-4PH SST
Wear Plate, Replaceable	Hardened steel
Cover Plate	Removable/Adjustable Gray Iron 30
Flap Valve	Neoprene with steel reinforcing ring
Bearing Housing	Ductile Iron
Seal Plate	Ductile Iron
Shaft Sleeve	SST 316
Radial Bearing	Open single ball
Thrust Bearing	Open double ball
Bearing/Seal Cavity Lubrication	SAE No. 30 oil
Flanges	125# Ductile iron ANSI or DIN
Gaskets	Buna-N, compressed synthetic fibers, vegetable fiber, PTFE, cork, and rubber
O-Rings	Buna-N - Teflon coated
Hardware	Plated steel
Pressure Release Valve	Brass
Oil Level Sight Guages	Bearing and Seal Cavity

Optional Equipment and Materials


Hi-Chrome, 316 SST, CD4MCU. Automatic air release valve, 120V/240V casing heater. High pump temperature shutdown kit, NPT & DIN standard suction and Discharge flanges.

Seal Specifications

Mechanical oil-lubricated, double floating, self-aligning seal. Silicon Carbide rotation and stationary faces. Stainless steel metal components. Maximum temperature of liquid pumped 180°F/83°C.

Note: consult factory for applications exceeding maximum pressure and/or temperature indicated.

Seal Detail View




Pump Specification: WSP6A



WEMCO[®] Self-Primer[™]

Pump Size	6"x6"/152mm x152 mm
Net Weight	800 lbs./260 KG.
Shipping Weight	850 lbs./300 KG
Export Crate	32 Cu. Ft./0.9 CU. M
Spool Flange	Add 35 lbs/16 KG. each



Suction: 6"
Discharge: 6"
Impeller Diameter: 12.38"
Max. Solid Sphere: 3.00"

REPRIMING LIFTS	
RPM	FEET
650	8
750	9
850	12
950	14
1050	18
1150-1250	21
1350	22
1450	23
1550	25

Determine NPSHR prior to using repriming table. Do not use available suction lifts.

$$BHP = \frac{GPM \times FT \times}{3960 \times Efficiency}$$

$$KW = \frac{M^3 / HR \times M}{367 \times Efficiency}$$

© Copyright
All rights reserved
WSP
SPECIALTY PUMPS

Certified tests are performed using Hydraulic Institute acceptance level A.

AUG. 2005

**RPM
VARIABLE**

WSP6A

